

# SMART.HUB™ SPECIFICATION

Type	SMART.HUB™
Height	7m-12m
Light Height	7m-10m
Diameter	168mm x 220mm
Maximum Weight	200 - 400kg
SMART.HUB™ Material Specification	
Material	Mild Steel Q345
Protective Coating	Hot Dipped Galvanised Min Local Thickness 70µm Min Average Thickness 85µm
Finish	Powder Coated Min Local Thickness 70µm Min Average Thickness 85µm
Cast Aluminium Brackets	
Material	Aluminium Grade CC601-T6
Finish	Powder Coated Min Local Thickness 70µm Min Average Thickness 85µm
Extruded Aluminium Outreach Arm	
Material	Aluminium Grade 6063-T6
Length	0.5m to 3m
Finish	Powder Coated Min Local Thickness 70µm Min Average Thickness 85µm
Fasteners	
Material	316 Stainless Steel
Colour	Clear

The SMART.HUB™ allows you to harness the potential of your lighting infrastructure and implement a range of innovative Smart City solutions. Elegantly designed and installed onto a fully capable SMART.NODE™ footing, the SMART.HUB™ allows you to step up to more advanced features as the need arises.

### Options

All SMART.HUB™ options are available with single/double outreach luminaires.

### Smart City Services Options



## SMART.HUB™ Drawings

